

Evo5 Light Finisher

In addition to the innovative automatic units, Vianord also offers the standard light finisher. This machine, for plates size up to 132 x 203 cm (52 x 80 inch), has the possibility to be installed either above the Evo 5 D or within the Evo processor units on either side at customer's preference.



LIGHT FINISHER FEATURES

- UVA + UVC lamps for post exposure and light finishing
- Programmable operation: simultaneous/separate/sequential
- Separate timers for UVA and UVC
- Automatic plate cooling with programmable time
- 24 programmable channels for different plate types
- Powerfull air exhaust with delayed stop for safe zone extraction
- Fiber optic lamp failure detectors
- Exhaust system integrated
- Touch screen operator display



Remote Monitoring
optional

Dimensions LxWxH



1740 x 2440 x 400 mm
68.5 x 96.1 x 17.7 inches

Power supply



400V 3PH/N/PE 50/60Hz 5.2kW 8.5A
230V 3PH/PE 50/60Hz 5.2kW 14A

Plate thickness



Up to 7 mm / 0.276 inch

Solvent



n/a

Packaging dimensions



1930 x 2650 x 1200 mm

Weight

350 kg | 770 pounds



Maximum plate size

132 x 203 cm | 52 x 80 inches



Compressed air supply

n/a



Exhaust

2 x 140 mm Ø - 600 m³/h



Packaging gross weights

520 Kg



Vianord
engineering
www.vianord.com
info@vianord.com

© 2015 Vianord. All rights reserved. The Vianord Logo®, Easy to Plate® and Evo® are registered trademarks or trademarks of Vianord Engineering SAS or its affiliates. All technical information set out herein is provided free of charge and is based on technical data, which Vianord believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Vianord Engineering SAS reserves the right to change the specifications of its products at any time. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.